

B601 AND GARMIN BMW NAVIGATOR VI

The B601 system is compatible via Bluetooth with the Garmin BMW Navigator VI. After pairing up and connecting the navigator to the N-Com system, you will be able to hear the signals coming from the Garmin in your helmet.

GARMIN BMW NAVIGATOR VI: software version 5.70

N-Com: B601 system, firmware version 1.0.1

GENERAL INFORMATION

PAIRING UP

For the pairing up procedure between N-Com and navigator, please refer to the user manual of the N-Com system, chapter "*Managing two mobile phones (or Bluetooth devices)*".

N.B.: For proper management of the various devices, the navigator must always be paired up with the N-Com system as a SECONDARY DEVICE (please refer to the user manual of the N-Com system, chapter "*Managing two mobile phones (or Bluetooth devices)*").

The Garmin BMW Navigator VI features two different pairing up options: *Mobile, Navigation* (HFP profile) and *Supports* (A2DP profile).

Mobile, Navigation + Supports: by activating both options, you can receive in your helmet phone calls, GPS indications, audio tracks coming from different sources (GPS internal memory, mobile phone, Mp3).

Mobile, Navigation: by activating only the Headset (HFP profile) option, you can receive in your helmet phone calls and GPS indications. You will NOT be able to listen to multimedia audio.

Supports: by activating only the Audio supports (A2DP profile) option, you can receive in your helmet multimedia audio. You will NOT be able to hear phone calls or GPS.

CONNECTION

Once the GPS has been paired up, connection takes place automatically upon switching on the B601 system.

N.B.: It is recommended to switch off the AUDIO PUSHBUTTONS on the navigator. With AUDIO PUSHBUTTONS active, with each command given on the Garmin, the navigator sends an acoustic feedback signal to the connected N-Com system, temporarily interrupting the playback of musical tracks and/or intercom communication between the two helmets.

INDIVIDUAL USE

The navigator must be paired up and connected to the rider helmet only, following the instructions provided in the "General" section.

GPS INDICATIONS

After pairing up and connecting the navigator to the N-Com system, you will be able to hear the audio signals coming from the Garmin BMW Navigator VI in your helmet.

MOBILE PHONE

For proper management of the various devices, the mobile phone must be paired up to the N-Com system as MAIN DEVICE.

For proper operation of all devices involved, it is recommended to NOT pair up and connect the mobile phone and navigator one to the other.

Incoming calls temporarily interrupt the connection with the navigator.

MUSIC

FROM THE NAVIGATOR: You will not be able to listen to audio tracks coming from the navigator.

FROM THE MOBILE PHONE: You will be able to listen to music coming from the phone. During a GPS indication, the audio track is temporarily paused.

USE IN PAIR

The navigator must be paired up and connected to the rider helmet only, following the instructions provided in the "General" section.

GPS INDICATIONS

The intercom connection is automatically interrupted with each indication coming from the navigator and restored at the end of said indication.

MOBILE PHONE

For proper management of the various devices, the mobile phone must be paired up to the N-Com system as MAIN DEVICE.

For proper operation of all devices involved, it is recommended to NOT pair up and connect the mobile phone and navigator one to the other.

Incoming phone calls automatically interrupt the connection with the navigator and the intercom connection.

MUSIC

FROM THE NAVIGATOR: During intercom connection, you will not be able to listen to audio tracks coming from the navigator.

FROM THE MOBILE PHONE: During connection to the navigator, you will be able to listen to music coming from the mobile phone and share it with your passenger through the "Music Sharing" function (if available). During a GPS indication, the audio track is temporarily paused, and the intercom connection is temporarily suspended.

UNIVERSAL INTERCOM

During the UNIVERSAL INTERCOM connection, the B601 system keeps the connection active only to the MAIN DEVICE (and not to the SECONDARY DEVICE). Hence it will not be possible to use the navigator.